

Quick Opening Valves

Manually operated ball valves are used to control water to small open-head extinguishing systems or in the trim on waterflow alarm valves, dry pipe valves or automatic water control valves.

The friction loss through these valves should be considered when they are used in hydraulically calculated extinguishing systems. Consult the manufacturer for details. Unless otherwise noted in the listing, these valves have 175 psi (1205 kPa) rated working pressure.

Model 220-T, 220-C, FBV-3, FBVS-3

<i>Product Designation</i>	<i>Description</i>	<i>Nominal Pipe Size, in.</i>	<i>Pressure Rating, psi (kPa)</i>	<i>Remarks</i>
220-T	Ball Valve	1/4, 3/8, 1/2, 3/4, 1, 1-1/4, 1-1/2, 2	600 (4135)	a
220-C	Ball Valve	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	600 (4135)	b
FBV-3	Ball Valve	1/4, 3/8, 1/2, 3/4, 1, 1-1/4, 1-1/2, 2	600 (4135)	a
FBVS-3	Ball Valve	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	600 (4135)	b

Remarks

- a. Valve supplied with female NPT pipe thread connections.
- b. Valve supplied with solder end connections.

Company Name:	Fortune Manufacturing Co Ltd
Company Address:	11F, No. 222, Sec. 5, Nanking E. Road, Taipei, Taiwan, R.O.C.
Company Website:	Not Available
New/Updated Product Listing:	No
Listing Country:	Taiwan
Certification Type:	FM Approved