



## HHXX7.EX9159

## Fittings, Cast Iron, Ductile Iron, Malleable Iron and Bronze Certified for Canada

[Page Bottom](#)

## Fittings, Cast Iron, Ductile Iron, Malleable Iron and Bronze Certified for Canada

[See General Information for Fittings, Cast Iron, Ductile Iron, Malleable Iron and Bronze Certified for Canada](#)

## SIGMA PIPING PRODUCTS CORP

EX9159

700 GOLDMAN DR

CREAM RIDGE, NJ 08514 USA

Ductile Iron Fittings fabricated with dimensional specifications in accordance with ANSI/ASME B16.3 Class 150

Model	Configuration	Size (in.)	Rated Pressure (psig)
—	90° Elbow, 45° Elbow, Tee, Cross, Straight Coupling, Cap	1, 1-1/4, 1-1/2, 2	500
—	Reducing Tee	1 x 1/2 x 1, 1 x 3/4 x 1, 1 x 1 x 1/2, 1 x 1 x 3/4, 1 x 1 x 1-1/4, 1 x 1 x 1-1/2, 1-1/4 x 1 x 1/2, 1-1/4 x 1 x 3/4, 1-1/4 x 1 x 1, 1-1/4 x 1 x 1-1/4, 1-1/4 x 1 x 1-1/2, 1-1/4 x 1-1/4 x 1/2, 1-1/4 x 1-1/4 x 3/4, 1-1/4 x 1-1/4 x 1, 1-1/4 x 1-1/4 x 1-1/2, 1-1/4 x 1-1/4 x 2, 1-1/2 x 1 x 1-1/2, 1-1/2 x 1 x 3/4, 1-1/2 x 1 x 1, 1-1/2 x 1 x 1-1/4, 1-1/2 x 3 x 1-1/2, 1-1/2 x 1-1/4 x 1/2, 1-1/2 x 1-1/4 x 3/4, 1-1/2 x 1-1/4 x 1, 1-1/2 x 1-1/4 x 1-1/4, 1-1/2 x 1-1/4 x 1-1/2, 1-1/2 x 1-1/4 x 2, 1-1/2 x 1-1/2 x 1/2, 1-1/2 x 1-1/2 x 3/4, 1-1/2 x 1-1/2 x 1, 1-1/2 x 1-1/2 x 1-1/4, 1-1/2 x 1-1/2 x 2, 2 x 1 x 2, 2 x 1-1/4 x 2, 2 x 1-1/2 x 1/2, 2 x 1-1/2 x 3/4, 2 x 1-1/2 x 1, 2 x 1-1/2 x 1-1/4, 2 x 1-1/2 x 2, 2 x 2 x 1/2, 2 x 2 x 3/4, 2 x 2 x 1, 2 x 2 x 1-1/4, 2 x 2 x 1-1/2	500
—	Reducing Elbow	1 x 1/2, 1 x 3/4, 1-1/4 x 1/2, 1-1/4 x 3/4, 1-1/4 x 1, 1-1/2 x 1, 1-1/2 x 1-1/4, 2 x 1/2, 2 x 3/4, 2 x 1, 2 x 1-1/4, 2 x 1-1/2	500
	Reducing Cross	1-1/4 x 1-1/4 x 1 x 1, 1-1/2 x 1-1/2 x 1 x 1, 2 x 2 x 1 x 1	500
—	Reducing Coupling	1 x 1/2, 1 x 3/4	500

Ductile Iron Fittings fabricated with dimensional specifications in accordance with ANSI B16.14

Model	Configuration	Size (in.)	Rated Pressure (psig)
—	Reducing Bushing	1 x 1/2, 1 x 3/4, 1-1/4 x 1, 1-1/2 x 1, 1-1/2 x 1-1/4, 2 x 1, 2 x 1-1/4, 2 x 1-1/2	500

**Cast Iron Threaded Fittings (ANSI/ASME B16.4) Class 125****Fittings fabricated with dimensional specifications in accordance with ANSI/ASME B16.4 and ANSI/ASME B16.14**

Model	Configuration	Size (in.)	Rated Pressure (psig)
—	45° Elbow	1, 1-1/4, 1-1/2, 2, 2-1/2	300
—	90° Elbow	1, 1-1/4, 1-1/2, 2, 2-1/2	300
—	Reducing Elbow	1 x 1/2; 3/4 1-1/4 x 1/2; 3/4, 1 1-1/2 x 1/2; 3/4, 1, 1-1/4 2 x 1/2; 3/4, 1, 1-1/4, 1-1/2	300
—	Tee	1, 1-1/4, 1-1/2, 2, 2-1/2	300
—	Reducing Tee	1 x 1 x 1/2; 3/4 1 x 1/2 x 1, 1 x 3/4 x 1 1 x 1 x 1-1/4, 1 x 1 x 1-1/2 1-1/4 x 1 x 1/2; 3/4 1-1/4 x 1 x 1; 1-1/4, 1-1/4 1-1/4 x 1-1/4 x 1/2; 3/4, 1, 1-1/2, 2 1-1/2 x 1 x 1/2; 3/4, 1, 1-1/4, 1-1/2 1-1/2 x 1-1/4 x 1/2; 3/4, 1, 2-1/4, 1-1/2, 2 1-1/2 x 1-1/2 x 1/2; 3/4, 1, 1-1/4, 2 2 x 1 x 2 2 x 1-1/4 x 2 2 x 1-1/2 x 1/2; 3/4, 1, 1-1/4, 1-1/2, 2 2 x 2 x 1/2; 3/4, 1, 1-1/4, 1-1/2, 2-1/2	300
—	Cross	1, 1-1/4, 1-1/2, 2, 2-1/2	300
—	Reducing Cross	1-1/4 x 1-1/4 x 1 x 1, 1-1/2 x 1-1/2 x 1 x 1, 2 x 2 x 1 x 1	300
—	Reducing Coupling	1 x 1/2; 3/4	300
—	Plug	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	300

Trademark and/or Tradename: "SPPC"

Last Updated on 2010-08-25[Questions?](#)[Print this page](#)[Terms of Use](#)[Page Top](#)

© 2012 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2012 UL LLC".